



**METAFRAX  
CHEMICALS**

## **AQUEOUS SODIUM FORMATE SOLUTION**

### **Application**

Product is used as additive to concrete and cement mortars in construction, as anti-frost and film forming additive in coal industry, as liquid for killing of wells during maintenance in drilling works.

### **Transportation and storage**

Product is transported in bulk in railway tank cars, in special tank containers via railway, in tank trucks and covered motor transport according to the cargo transportation norms valid for the mode of transport. Product is stored in tanks made of stainless steel of 12X18H10T grade, carbon steels with subsequent epoxy resin coating. Packed in medium weight containers for mass products the material is stored in covered storages protected against direct sunlight.

### **Manufacturer's guaranty**

Guaranty period of storage to be 1 year from the manufacturing date, provided that all transportation and shipment rules are observed.

### **Purchasing of the product**

PJSC Metafrax  
Maksim Zagrebin  
Phone: +7 342 489 25 89  
Fax: +7 342 484 72 27  
E-mail: [Sale@metafrax.ru](mailto:Sale@metafrax.ru)



**METAFRAX  
CHEMICALS**

### Main physical and chemical features

Parameter name	Norm
Appearance	Fluid with light-yellow to light-green colour with fine suspension sediment
Density, at 20°C, kg/m <sup>3</sup> , above	1170
Mass fraction of sodium formate, %	20 – 30
Volume fraction of suspended particles, %, no more	90
pH value	7,0 – 9,0